



GST Leaching System

37" Series

| Product Name | Dimensions (W x H) | Effective Leaching Credit (SF/LF) | Center to Center Spacing (feet) | Storage Volume Gallons per LF |
|--------------|--------------------|-----------------------------------|---------------------------------|-------------------------------|
| GST 3706 | 37" x 6" | 3.6 | 8 | 3.05 |
| GST 3712 | 37" x 12" | 5.9 | 10 | 6.11 |
| GST 3718 | 37" x 18" | 8.2 | 10 | 9.16 |
| GST 3724 | 37" x 24" | 10.5 | 12 | 12.22 |
| GST 3730 | 37" x 30" | 12.9 | 12 | 15.27 |
| GST 3736 | 37" x 36" | 15.2 | 12 | 18.32 |

62" Series

| Product Name | Dimensions (W x H) | Effective Leaching Credit (SF/LF) | Center to Center Spacing (feet) | Storage Volume Gallons per LF |
|--------------|--------------------|-----------------------------------|---------------------------------|-------------------------------|
| GST 6206 | 62" x 6" | 5.9 | 12 | 4.52 |
| GST 6212 | 62" x 12" | 10.0 | 12 | 9.23 |
| GST 6218 | 62" x 18" | 14.0 | 13 | 13.84 |
| GST 6224 | 62" x 24" | 18.1 | 13 | 18.45 |
| GST 6230 | 62" x 30" | 22.1 | 13 | 23.06 |
| GST 6236 | 62" x 36" | 26.2 | 13 | 27.68 |

Stone and Sand Volume Guide

37" Series

| Product Name | Amount of DOT No. 6 ¾" Stone Required | Amount of ASTM C-33 Sand Required |
|--------------|---------------------------------------|-----------------------------------|
| | Yards per. Linear Foot | |
| GST 3706 | 0.16 | 0.18 |
| GST 3712 | 0.19 | 0.25 |
| GST 3718 | 0.22 | 0.32 |
| GST 3724 | 0.25 | 0.39 |
| GST 3730 | 0.28 | 0.46 |
| GST 3736 | 0.31 | 0.53 |

62" Series

| Product Name | Amount of DOT No. 6 ¾" Stone Required | Amount of ASTM C-33 Sand Required |
|--------------|---------------------------------------|-----------------------------------|
| | Yards per Linear Foot | |
| GST 6206 | 0.20 | 0.25 |
| GST 6212 | 0.27 | 0.35 |
| GST 6218 | 0.35 | 0.46 |
| GST 6224 | 0.43 | 0.56 |
| GST 6230 | 0.50 | 0.66 |
| GST 6236 | 0.58 | 0.76 |

NOTE: Amount, of stone calculated to fill form and to provide 6" over GST to accommodate distribution pipe. Installer is responsible for ordering additional necessary stone to account for spillage, etc. **STONE MUST BE WASHED & CLEAN!**

NOTE: Amount of sand calculated to fill the form, a base of 4" and a 4" perimeter around the form. Installer is responsible for ordering additional sand for larger and/or irregularly shaped excavations, to account for spillage, etc. **MUST MEET ASTM C-33 SPEC.**

114 Mill Rock Road East – Old Saybrook, CT 06475
Phone: 860-510-0730 – Fax: 860-510-0735

Geomatrix products are manufactured under one or more of the following U.S. patents; 6,485,647, 6,726,401, 6,814,866, 6,887,383, 6,923,905, 6,959,882, 6,969,464, 7,157,011, 7,309,434, 7,351,005, 7,374,670, 7,465,390, 7,744,759 - April 2011 All rights reserved